

- **High Drain
Lithium Thionyl Chloride (Li-SOCl₂) Battery**

CYLINDRICAL CELLS (SPIRAL TYPE)

Model	Cell Size Ref.	Rated Voltage	Nominal Capacity	Nominal Discharge Current	Maximum Recommended Continuous Current	Maximum Pulse Current Capability	Operating Temperature Range	Maximum Dimensions		Weight
								Diameter	Height	
ER14250HD	1/2AA	3.6V	0.80Ah	2.0mA	100mA	350mA	-40°C~+85°C	14.5mm	25.4mm	10g
ER14335HD	2/3AA	3.6V	1.35Ah	3.0mA	150mA	500mA	-40°C~+85°C	14.5mm	33.5mm	13g
ER14505HD	AA	3.6V	2.20Ah	4.0mA	400mA	1,000mA	-40°C~+85°C	14.5mm	50.5mm	19g
ER18505HD	A	3.6V	3.50Ah	5.0mA	600mA	1,500mA	-40°C~+85°C	18.5mm	50.5mm	28g
ER26500HD	C	3.6V	6.50Ah	10.0mA	800mA	2,000mA	-40°C~+85°C	26.2mm	50.0mm	52g
ER34615HD	D	3.6V	13.00Ah	15.0mA	1,800mA	4,000mA	-40°C~+85°C	32.9mm	61.5mm	100g