

- **Safe Plus**
Lithium Thionyl Chloride (Li-SOCl₂) Battery

CYLINDRICAL CELLS (SPIRAL TYPE)

Model	Cell Size Ref.	Rated Voltage	Nominal Capacity	Nominal Discharge Current	Maximum Recommended Continuous Current	Maximum Pulse Current Capability	Operating Temperature Range	Maximum Dimensions		Weight
								Diameter	Height	
ER14250SP	1/2AA	3.6V	0.75Ah	2.0mA	100mA	350mA	-40°C~+85°C	20.0mm	27.5mm	12g
ER14335SP	2/3AA	3.6V	1.35Ah	3.0mA	150mA	500mA	-40°C~+85°C	20.0mm	36.0mm	15g
ER14505SP	AA	3.6V	2.15Ah	4.0mA	400mA	1,000mA	-40°C~+85°C	20.0mm	51.0mm	21g
ER18505SP	A	3.6V	3.40Ah	5.0mA	600mA	1,500mA	-40°C~+85°C	24.0mm	51.0mm	28g
ER26500SP	C	3.6V	6.30Ah	10.0mA	800mA	2,000mA	-40°C~+85°C	31.0mm	52.0mm	57g
ER34615SP	D	3.6V	12.50Ah	15.0mA	1,800mA	4,000mA	-40°C~+85°C	37.0mm	63.0mm	100g